

OUTDOOR LIGHTING

LED Street Lights Roadway Series 2nd Gen



Optional Pole Attachments



140006



140003



140005



140004



106674

FEATURES

- Dark Sky Friendly, IDA Approved.
- CREE LED chip
- Dimmable
- Photocell available
- Salt air and fog resistant
- 120 lumens per watt efficiency
- IP66 for wet locations
- Tool-less entry
- Great for government and municipalities, roadways, parking lots, highways, walkways and general area

One piece die-cast aluminum housing with integral heatsink fins to optimize thermal management through conductive and convective cooling. Modular design allows for ease of maintenance. The LED driver is mounted to the door to thermally isolate it from the light engines. It is isolated for low operating temperature and long life. Housing is completely sealed against moisture and environmental contaminants. This solution enables significant operating cost benefits over the life of each fixture by reducing energy and maintenance expenses.

SPECIFICATIONS

LED Street Lights Roadway Series -2nd Gen Street Light

Item#/SKU	Model#	Watts	Lumens	Qualified	Pcell	CCT	IP	CRI	Input Voltage	Size	Operating Temperature	Life Span
106484	106484	120W	13790lm	UL & DLC	No	5700K	66	>70	110-277V	22.5"X13"5.3"	-31°/122°F	50,000hrs
106476	106476	240W	26300lm	UL & DLC	No	5700K	66	>70	110-277V	22.5"X13"5.3"	-31°/122°F	50,000hrs
106617	106617	240W	26300lm	UL & DLC	Yes	5700K	66	>70	110-277V	22.5"X13"5.3"	-31°/122°F	50,000hrs