

OUTDOOR LIGHTING

LED Wall Packs

STA Series



FEATURES

- Improves light uniformity and visibility
- Full spectrum lighting (mimics sunlight)
- Brown finish with visor
- Uses CREE XTE LED chip
- Efficiency over 90 lumens per watt
- IP 65
- Power Factor: >.9
- Beam Angle: 120° (Narrow 60° available)
- Aluminum alloy housing
- UL listed
- 50,000 hour life span




HL Series



FEATURES

- Replaces up to 400W MH
- High performance Samsung chip
- Tempered glass lens
- Bronze finish
- Surface mounting with J-Box
- Efficiency over 100 lumens per watt
- IP 65 great for wet locations
- Power Factor: >.95
- Aluminum alloy housing
- ETL listed
- 50,000 hour life span



SPECIFICATIONS

STA Series - Traditional Wall Packs

Item#/SKU	Model#	Watts	Lumens	Qualified	CCT	CRI	IP	Beam Angle	Input Voltage	Dimensions	Lifespan
105486-1	BLTWP50W57KWM	50W	5800lm	UL & DLC	5700K	>75	65	120°	100-277V	14.2"X 9.3"X7.4"	50,000 hrs
104281	BLTWP80W57KWM	80W	9800lm	UL & DLC	5700K	>75	65	120°	100-277V	14.2"X 9.3"X7.4"	50,000 hrs
104885	BLTWP120W57KWM	120W	13520lm	UL & DLC	5700K	>75	65	120°	100-277V	14.2"X 9.3"X7.4"	50,000 hrs

HL Series - Traditional Wall Packs

109694	BLTWP080W5KHLS	80W	9600lm	ETL & DLC	5000K	>70	65	120°	100-277V	14.2"X 9.3"X7.4"	50,000 hrs
109686	BLTWP100W5KHLS	100W	11000lm	ETL & DLC	5000K	>70	65	120°	100-277V	14.2"X 9.3"X7.4"	50,000 hrs

Rotatable Wall Packs

110718	BLTRWP60W57K	60W	8100lm	UL/DLC	5700K	>70	65	60°	96-300V	9.1"X5.1"X8.8"	50,000 hrs
110726	BLTRWP80W57K	80W	10800lm	UL/DLC	5700K	>70	65	60°	96-300V	9.1"X5.1"X8.8"	50,000 hrs

HRE Series Door Wall Packs

109702	BLTWP018W5KH	18W	2000lm	ETL & DLC	5000K	>70	65	120°	100-277V	9.1"X 3.0"X4.0"	50,000 hrs
109710	BLTWP026W5KH	26W	2860lm	ETL & DLC	5000K	>70	65	120°	100-277V	9.1"X 3.0"X4.0"	50,000 hrs